

LineLazer Specifications

		LineLazer ES 1000	LineLazer 3400	LineLazer 130HS	LineLazer V 3900	LineLazer V 5900	LineLazer V 200HS	LineLazer V 250SPS	LineLazer V 250DC
SPECIFICATIONS	Maximum Tip Size	0.025	0.027	0.037	0.036	0.043	0.047	0.055	0.055
	Maximum psi (bar)	3300 (227)	3300 (227)	3300 (227)	3300 (227)	3300 (227)	3300 (227)	3300 (227)	3300 (227)
	Maximum gpm (lpm)	0.60 (2.3)	0.75 (2.8)	1.30 (4.9)	1.25 (4.7)	1.60 (6.0)	2.15 (8.14)	2.50 (9.5)	2.50 (9.5)
	Applications	Turf & Pavement	Turf & Pavement	Turf & Pavement	Turf & Pavement	Turf & Pavement	Turf & Pavement	Turf & Pavement	Turf & Pavement
	Honda GX Engine cc (hp)	N/A	120 (4.0)	120 (4.0)	120 (4.0)	160 (5.5)	200 (6.5)	390 (13.0) Electric Start	390 (13.0) Electric Start
	Weight lb (kg)	340 (154) - p/n 25M226 410 (186) - p/n 25M315	160 (73)	263 (119)	230 (104) Standard Unit 240 (109) HP Automatic Units	250 (113) Standard Unit 266 (121) HP Automatic Units	306 (139) Standard Unit 322 (146) HP Automatic Units 417 (153) HP Reflective Unit with Pressure Bead System-1 Tank	666 (302) HP Automatic Units 778 (352) HP Reflective Unit with Pressure Bead System-2 Tanks	752 (341) HP Automatic Units 864 (392) HP Reflective Units with Pressure Bead System-2 Tanks
	Gun Support: 1 Gun 2 Guns 3 Guns 4 Guns 5 Guns	0.025 0.019 — — —	0.027 — — — —	0.037 0.029 — — —	0.036 0.025 — — —	0.043 0.029 — — —	0.047 0.034 — — —	0.055 0.039 0.031 0.025 0.021	0.055 0.039 0.031 0.025 0.021



SERIES TYPE		EPOWER	STANDARD	STANDARD	STANDARD	HP AUTOMATIC		STANDARD	HP AUTOMATIC		STANDARD	HP AUTOMATIC		HP REFLECTIVE	HP AUTOMATIC	HP REFLECTIVE		HP AUTOMATIC		HP REFLECTIVE	
MODEL	Part Number	25M226 – 1 Battery 25M315 – 2 Battery	25M224	17H448	17H450	17H452	17H453	17H455	17H457	17H458	17H461	17H463	17H464	17H465	17H467	17J951	17H469	17H471	17H472	17H473	17H474
INCLUDES	Gun(s)	Flex Plus	Flex Plus	Flex Plus	FlexPlus 2 Manual	FlexPlus 1 Automatic, 1 Manual	Flex Plus 2 Automatic	Flex Plus 2 Manual	Flex Plus 1 Automatic, 1 Manual	Flex Plus 2 Automatic	Flex Plus 2 Manual	Flex Plus 1 Automatic, 1 Manual	Flex Plus 2 Automatic	Flex Plus 2 Automatic, PBS INSTALLED 1 TANK	Flex Plus 2 Automatic	Flex Plus 2 Automatic, PBS INSTALLED 1 TANK	Flex Plus 2 Automatic, PBS INSTALLED 2 TANKS	Flex Plus 2 Automatic	Flex Plus 3 Automatic	Flex Plus 2 Automatic, PBS INSTALLED 2 TANKS	Flex Plus 3 Automatic, PBS INSTALLED 2 TANKS
	Hose	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	3/8 in x 22 ft (9.5 mm x 6.7 m) BlueMax II Airless	3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Airless			3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Airless			3/8 in x 22 ft (9.5 mm x 6.7 m) BlueMax II Airless				3/8 in x 22 ft (9.5 mm x 6.7 m) BlueMax II Airless			3/8 in x 12 ft 2X (9.5 mm x 3.7 m) BlueMax II Airless			
	SwitchTip	LineLazer RAC 5	LineLazer RAC 5	LineLazer RAC 5	LineLazer RAC 5			LineLazer RAC 5			LineLazer RAC 5				LineLazer RAC 5			LineLazer RAC 5			
	Easy Out Filter	60 Mesh	60 Mesh	50 Mesh	50 Mesh			50 Mesh			50 Mesh				50 Mesh			50 Mesh			
PUMP	Type	ProConnect	QuikChange System	QuikChange System	QuikChange System			QuikChange System			QuikChange System				QuikChange System			QuikChange System			
	Intake	QuikAccess	QuikAccess	QuikAccess	QuikAccess			QuikAccess			QuikAccess				QuikAccess			QuikAccess			
	Rod	Chromex	Chromex	Chromex	Chromex			Chromex			Chromex				Chromex			Chromex			
	Cylinder	Hardened SST	Hardened SST	Hardened SST	Hardened Stainless Steel			Hardened Stainless Steel			Hardened Stainless Steel				Hardened Stainless Steel			Hardened Stainless Steel			
	Packings	V-Max Blue	V-Max Blue	V-Max Blue	V-Max Blue			V-Max Blue			V-Max Blue				V-Max Blue			V-Max Blue			
TRACKING FUEL TANK	Tracking System	N/A	N/A	N/A	SmartControl			SmartControl			SmartControl				SmartControl			SmartControl			
	Fuel Capacity gal (ltrs)	N/A	0.66 (2.5)	0.66 (2.5)	0.66 (2.5)			0.95 (3.6)			0.95 (3.6)				1.40 (5.3)			1.40 (5.3)			

LineDriver Specifications

		LineDriver	LineDriver HD
MODEL	Part Number	262004	262005
SPECIFICATIONS	Operating SpeedForward mph (km/h) Reverse mph (km/h)	to 10 (16) to 6 (10)	to 10 (16) to 6 (10)
	Honda GX Engine Size cc (hp)	160 (5.5)	200 (6.5)
	Weight lb (kg)	265 (120)	275 (125)
	Fuel Capacity gal (ltr)	.95 (3.6)	.95 (3.6)
	Engine Starting System	Manual Pull	ProStart



GSHP

GARDEN STATE HIGHWAY PRODUCTS, INC.
800.338.5685 • 856.692.7572 • www.gshpinc.com